Calculo K-80W

PORTABLE ELECTRONIC CALCULATOR

OWNERS REFERENCE MANUAL



INTRODUCTION

Your K-80W Electronic Calculator represents a significant engineering achievement resulting in full-size capability in a compact package. Major advances in miniaturized computer circuits using single-chip LSI (Large Scale Integration) have provided a rugged and reliable unit, and the self-contained rechargeable battery pack permits convenient use without need for AC power. An AC adapter is available for AC operation and/or recharging.

The K-80W will perform addition, subtraction, multiplication, and division functions, including chain or mixed multiplication and divisions, and utilization of stored constant. Eight digits are provided for entry and read-out, with full-floating or fixed decimal point selection, and positive or negative sign capability. Additional display indicators denote overflow, error, and negative result (minus sign). A meter indicates battery condition when the unit is in use.

It is suggested that the following instructions for operation be read with the calculator at hand, and that all calculation examples be performed to increase your familiarity with the unit.

PREPARATION FOR USE

Battery Power

A rechargeable battery pack is permanently installed in the calculator. A full charge allows at least 3 hours operating time.

AC Power

The calculator may be operated from any AC 50/60 Hz outlet by using the AC Adapter. Plug the adapter into a convenient wall receptacle, and insert the small connecter into the "DC 6V" socket on the back of the calculator.

Battery Recharge

The batteries in the calculator are automatically connected to a recharging circuit whenever the AC Adapter is in use, regardless of the position of the calculator power switch.

When operating the unit on battery, observe the battery check meter. When the pointer passes into the red area of the scale the battery should be recharged by leaving the unit plugged into the AC line overnight. A fully discharged battery may take 24 hours to recharge. Nickel-cadmium cells will not be damaged by moderate over- charging. However, if the K-80W is to be left unused for more than few days, it is desirable to unplug the power cord.

Warning

Do not store the calculator in high-temperature areas such as the top of a room heater or the rear package shelf of an automobile exposed to the sun. Satisfactory operation should be obtained over an ambient temperature range of 0 to 50 C (32 to 122F), and relative humidity to 95%. Do not immerse or allow liquids to fall on the unit.

CONTROLS & INDICATORS

| Power and "K" Switch | Turns calculator power "ON" & "OFF". Slide switch with 3 positions; in the top position, the "K" operation is in effect. Use of "K" allows a number to be entered and retained as a "constant" for series multiplication or division. |
|----------------------|--|
| Decimal Switch | Three-position slide switch selects number of decimal positions in answer. "AUTO" places decimal in appropriate position required by calculation. "2" and "3" provide fixed decimal answers, with automatic round-off of additional decimal digits. When the next digit is 0 - 4, the last displayed digit is not changed. When the next digit is 5 - 9, the last displayed digit is increased by 1. |
| CKey | Clears the calculator and the display of all numbers. |
| CE Key | Clears last entry (Error correction) |
| XKey | Enters a "multiply" command. |
| - Key | Enters a ''divide'' command. |
| ± Key | Adds the entered number, or carries out a previously entered "multiply" or "divide" command. |
| +/- Key | Reverse setting of figures from Negative to Positive or vice versa. |
| -= Key | Adds a minus sign to an entry. Subtracts the entered number or completes a previously entered "multiply" or "divide" command. |
| . Key | Enters a decimal point. |
| 0-9 Keys | Enters digits of a number (limit 8 digits). |
| Overflow Indicator | Indicates a calculation result that contains more than eight digits. Appears as |
| Minus Sign Indicator | Activated by the - = Key for operations with negative numbers. |
| Error Indicator | Indicates an entry of more than 8 digits |

Appears as

CALCULATIONS

h. ENTER 40 -

TOUCH[-=

1.

| CALCULATIONS | |
|---|--|
| 1. ADDITION | |
| EXAMPLE: TO CALCULATE 16 + 9 + 8.3 + 4.1 = | |
| DO THESE STEPS | DISPLAY WILL BE |
| a. TOUCH C | <u>0.</u> |
| b. ENTER 16 | 16. |
| c. TOUCH = | <u> </u> |
| d. ENTER 9 | 9. |
| e. TOUCH = | 25. |
| f. ENTER 8.3 | 8.3 |
| g. TOUCH [±] | 33.3 |
| h. ENTER 4.1 | 4.1 |
| i. TOUCH ANSWER | 37.4 |
| 2. SUBTRACTION | |
| EXAMPLE #1: TO CALCULATE 12.81 - 3.6 = | |
| DO THESE STEPS | DISPLAY WILL BE |
| a. TOUCH C | — [|
| b. ENTER 12.81 | — 12.81 |
| c. TOUCH = | — 12.81 |
| d. ENTER 3.6 | - 3.6 |
| e. TOUCH = ANSWER | 9.21 |
| EXAMPLE #2: TO CALCULATE 23 - 6 + 2.1 - 5 = | |
| DO THESE STEPS | DISPLAY WILL BE |
| a. TOUCH C | —[0.] |
| b. ENTER 23 ——————————————————————————————————— | |
| c. TOUCH = | — 23. |
| d. ENTER 6. | — 6. T |
| e. TOUCH == | |
| f. ENTER 2.1 | — 2.1 |
| g. TOUCH = | 19.1 |
| h. ENTER 5 | |
| i. TOUCH = ANSWER | 14.1 |
| EXAMPLE #3: TO CALCULATE 62 - 82 + 10 - 40 | |
| DO THESE STEPS | DISPLAY WILL BE |
| a. TOUCH C | — O. |
| b. ENTER 62 | 62. |
| c. TOUCH = | 62. |
| d. ENTER 82 | 82. |
| e. TOUCH [-=] | —————————————————————————————————————— |
| f. ENTER 10 | |
| g. TOUCH = | |
| y. 1000⊓(<u>±</u>) | 10. |

40.

50.

| 3. | REVERSE SETTING +/- | |
|----|--|-----------------|
| | EXAMPLE: TO CALCULATE 62 - 82 = -20, | |
| | Reverse setting $+/-:$ $-20 = +20 + 30 =$ | 25 |
| | DO THESE STEPS | DISPLAY WILL BE |
| | a. TOUCH [C] | O.] |
| | b. ENTER 62 | 62. |
| | c. TOUCH[±] | — [62. |
| | d. ENTER 82 | 82. |
| | e. TOUCH[=] | <u> </u> |
| | f. TOUCH[+/-] | |
| | g. TOUCH = | |
| | h. ENTER 30 | — 30. |
| | i. TOUCH = ANSWER | 50. |
| 4. | MULTIPLICATION | |
| | EXAMPLE #1: TO CALCULATE 29.32 x 56.5 = | |
| | DO THESE STEPS | DISPLAY WILL BE |
| | a. TOUCH C | O.] |
| | b. ENTER 29.32 | 29.32 |
| | c. TOUCH X | - 29.32 |
| | d. ENTER 56.5 | 56.5 |
| | e. TOUCH = ANSWER | 1656.58 |
| | EXAMPLE #2: TO CALCULATE 3 x 21 x 6.1 = | |
| | DO THESE STEPS | DISPLAY WILL BE |
| | a. TOUCH C | O.] |
| | b. ENTER 3 ——————————————————————————————————— | 3. |
| | c. TOUCH X | |
| | d. ENTER 21 | — 21. |
| | e. TOUCH X | 63. |
| | f. ENTER 6.1 | 6.1 |
| | g. TOUCH = ANSWER | 384.3 |
| | EXAMPLE #3: TO CALCULATE 13 x 6 = | |
| | USE OF 'K' SWITCH 31 x 8.2 = | |
| | 31 x 7.6 = | |
| | DO THESE STEPS | DISPLAY WILL BE |
| | a. TOUCH C | – 0. |
| | b. PUSH POWER SWITCH TO "K" | O. |
| | c. ENTER 31 | 31. |
| | d. TOUCH X | 31. |
| | e. ENTER 6 | 6. |
| | f. TOUCH = 1st ANSWER | 186. |
| | g. ENTER 8.2 | 8.2 |
| | h. TOUCH = 2nd ANSWER | 254.2 |
| | i. ENTER 7.6 ——————————————————————————————————— | 7.6 |
| | j. TOUCH = 3rd ANSWER | 235.6 |
| | k. PUSH 'K' OFF (POWER SWITCH "ON") | |
| | | |

| DIVISION | |
|---------------------------------------|-----------------|
| EXAMPLE #1: TO CALCULATE 376 ÷ 53 = | |
| DO THESE STEPS | DISPLAY WILL BE |
| a. TOUCH C | — [0. |
| b. ENTER 376 | — 376. |
| c. TOUCH : | — 376. |
| d. ENTER 53 | 53. |
| e. TOUCH = ANSWER | 7.0943396 |
| EXAMPLE #2: TO CALCULATE 81 ÷ 3 ÷ 9 = | |
| DO THESE STEPS | DISPLAY WILL BE |

| DO THESE STEPS | DISPLAY WILL BE |
|-------------------|-----------------|
| a. TOUCH C | O . |
| b. ENTER 81 | 81. |
| c. TOUCH [÷] | 81. |
| d. ENTER 3 | 3. |
| e. TOUCH : | 27. |
| f. ENTER 9 | 9. |
| g. TOUCH = ANSWER | 3. |

EXAMPLE #3: TO CALCULATE 181 ÷ 15 =

USE OF 'K' SWITCH 96 ÷ 15 =

117 ÷ 15 =

| DO THESE STEPS | DISPLAY WILL BE |
|-------------------------------------|-------------------|
| a. TOUCH C | — [0.] |
| b. PUSH POWER SWITCH TO "K" | — [0.] |
| c. ENTER 181 | — [181.] |
| d. TOUCH : | 181. |
| e. ENTER 15 | [15.] |
| f. TOUCH = 1st ANSWER | 12.066666 |
| g. ENTER 96 | 96. |
| h. TOUCH = 2nd ANSWER | 6.4 |
| i. ENTER_117 | |
| j. TOUCH = 3rd ANSWER | 7.8 |
| k. PUSH 'K' OFF (POWER SWITCH "ON") | |

6. MIXED ARITHMETIC

EXAMPLE #1: TO CALCULATE 23 x (-4) - (-6) =

| DO THESE STEPS | DISPLAY WILL READ |
|-----------------|-------------------|
| a. TOUCH [C] | O. |
| b. ENTER 23 | 23. |
| c. TOUCH X | |
| d. ENTER 4 | 4. |
| e. TOUCH[-=] | 92. |
| f. TOUCH 🚉 ———— | 92. |
| g. ENTER 6 | 6. |
| h. TOUCH = | 15.333333 |

EXAMPLE #2: TO CALCULATE $\frac{(9+6-5)\times 8}{20}$ - 8 =

| | DO THESE STEPS | DISPLAY WILL BE |
|---|-----------------|-----------------|
| | a. TOUCH[C] | O. |
| | b. ENTER 9 | 9. |
| | c. TOUCH [t] | 9. |
| Ē | d. ENTER 6 | — 6. |
| • | e. TOUCH = | 1 5. |
| | f. ENTER_5 | |
| | g. TOUCH = | [10. |
| | h. TOUCH X | |
| | i. ENTER 8 | 8. |
| | j. TOUCH ÷ | 80. |
| | k. ENTER 20 | 20, |
| | I. TOUCH ± | 4. |
| | m. ENTER 8 | 8. |
| | n. TOUCH ANSWER | _ 4. |

7. EXPONENTS

EXAMPLE #1: TO CALCULATE (3)5 =

| DO THESE STEPS | DISPLAY WILL BE |
|------------------------------------|-----------------|
| a. TOUCH C | O. |
| b. PUSH POWER SWITCH TO "K" | O. |
| c. ENTER 3 | 3. |
| d. TOUCH X | 3. |
| e. TOUCH = | 9, |
| f. TOUCH = | 27. |
| g. TOUCH ± | 81. |
| h. TOUCH = ANSWER | 243. |
| i. PUSH 'K' OFF (POWER SWITCH "ON" |) |

EXAMPLE #2: TO CALCULATE $6 \div (3)^3 =$

| DO THESE STEPS | DISPLAY WILL BE |
|-------------------------------------|-----------------|
| a. TOUCH C | — [O.] |
| b. PUSH POWER SWITCH TO "K" | O. |
| c. ENTER <u>6</u> | 6. |
| d. TOUCH 🗄 ————— | 6. |
| e. ENTER <u>3</u> | 3. |
| f. TOUCH = | 2. |
| g. TOUCH ± | 0.666666 |
| h. TOUCH ± ANSWER | 0.222222 |
| i. PUSH 'K' OFF (POWER SWITCH "ON") | |

OPERATION OUTLINE

(REFER TO INSTRUCTION MANUAL FOR COMPLETE INFORMATION)

BATTERIES RECHARGEABLE BATTERY PACK INSTALLED.

POWER SLIDE POWER SWITCH TO "ON". DO NOT MOVE TO "K" (CONSTANT) POSITION UNLESS REQUIRED FOR CALCULATIONS. WHEN AC ADAPTER IS USED, RE-

CHARGEABLE BATTERIES WILL CHARGE EVEN WHEN

POWER SWITCH IS "OFF".

DECIMAL SET TO "AUTO" FOR FLOATING DECIMAL. SET TO "2" I.E. 4.555 → 4.56 OR 4.544 → 4.54

SET TO "3" I.E. 4.5555 → 4.556 OR 4.5554 → 4.555.

INDICATORS E SHOWS INPUT EXCEEDS 3 DIGITS. CALCULATIONS MAY PROCEED USING 8 MOST-SIGNIFICANT DIGITS.

> " SHOWS RESULT EXCEEDS 8 DIGITS. CALCULATION STOPPED, AND ANSWER CORRECT WHEN DECIMAL MOVED 8 PLACES TO RIGHT OF DISPLAYED

POSITION.

METER - WHEN POINTER STAYS IN RED ZONE, RE-

CHARGE BATTERIES, OR USE AC ADAPTER.

CALCULATIONS ALWAYS BEGIN BY PUSHING [C]

IF MISTAKE IS MADE IN ENTRY, CE KEY WILL CLEAR ENTRY BUT NOT ACCUMULATOR.

A+B=X ENTER A, (H=); ENTER B, (H=); READ X. A-B=X ENTER A, (H=); ENTER B, (H=); READ X.

AxB=X ENTERA, X; ENTERB, +=; READ X.

(-A)xB=X ENTER A, 于三区; ENTER B, 于三; READ X.

Ax(-B)=X ENTER A, X; ENTER B, H= ; READ

A÷B=X ENTERA, ☐; ENTERB, ☐ READ X.

USING CONSTANT (POWER SWITCH AT "K")

KxA=XENTER K, X; ENTER A, +=; READ X.

KxB=Y ENTER B, H=; READ Y.

 KxC=Z
 ENTER C,
 田;
 READ Z.

 A³=X
 ENTER A,
 区;
 田;
 READ X.

 A÷K=X
 ENTER A,
 豆;
 ENTER K,
 田;
 READ X.

B÷K=Y ENTER B, $\pm =$; READ Y.

ENTER C, ==; READ Z. C÷K=Z

🗄; 旺, ENTER A, I/A=X+=; READ X.